



HYTRONIK®

HYTRONIK INDUSTRIAL LIMITED
Room D, 10/f, Tower A, Billion Center, 1 wang Kwong Road,
Kowloon Bay, Kowloon, Hongkong
T: 00852-35197525 F: 00852-30116936
E: info@hytronik.com

CHINA FACTORY
Pude Industrial Park, Dushi Village, Pingtan Town
Huiyang District Huizhou City Guangdong, P.R.C. 516295
Tel:86-752-2772020 F:86-752-2777877
E: info@hytronik.com W:www.hytronik.com

PRECAUTIONS FOR EMERGENCY Ni-Cd & Ni-MH BATTERY USAGE

STORAGE CONDITIONS

1. Temperature range for storage (Humidity: Max. 85%) 0 ~ +35°C , one year storage
(Storage time will be shortened if out of this temp. range)
2. Storage duration before use: Less than 6 months from batteries received to start with charging.

Note 1: For Ni-Cd battery, we recommend batteries are charged and discharged at least once every 6 months.

Note 2: For Ni-MH battery, we recommend batteries are charged and discharged at least once every 3 months.

Note 3: Never over discharge the battery.

WARNING

- a) Avoid direct soldering onto cells.
- b) Use only within the specified working temperature range.
- c) Do not subject batteries to mechanical shock.

DANGER!

- a) Avoid throwing cells into a fire or attempting to disassemble them. As the electrolyte inside is strong alkaline and can damage skin and clothes.
- b) Avoid short circuiting. It may be leakage.